

Spezifikation für Freigabe / specification for release

Kunde / customer:

Artikelnummer / part number:

744392200

LF




Bezeichnung : **SPEICHERDROSSEL WE-HCF**

description : **POWER-CHOKE WE-HCF**

DATUM / DATE : 2004-10-11

A Mechanische Abmessungen / dimensions:




● = Start of winding Marking = Inductance code

A	12,5 ± 0,3	mm
B	12,5 ± 0,3	mm
C	5,0 ± 0,3	mm
D	1,9 ± 0,2	mm

B Elektrische Eigenschaften / electrical properties:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Leerlaufinduktivität Initial Inductance	100 kHz / 1,0V	L	2,00	μH	± 25%
Induktivität inductance	at flat point	L _F	1,80	μH	± 25%
DC-Widerstand / DC-resistance	@ 20°C	R _{DC typ}	4,10	mΩ	typ.
DC-Widerstand / DC-resistance	@ 20°C	R _{DC max}	4,60	mΩ	max.
Nennstrom / rated current	ΔT=40 K	I _N	12,0	A	max.
Sättigungsstrom/ saturation current	ΔL/LF < 20%	I _{SAT}	13,0	A	typ.
Eigenres.-Frequenz / self-res.-frequency		SRF	49,0	MHz	typ.

C Lötpad / soldering spec.:



D Prüfgeräte / test equipment:

HP 4274 A für/for L und/and Q

HP 34401 A für/for I_{DC} und/and R_{DC}

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
Umgebungstemperatur / temperature: +20°C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: Ferrit / ferrite
Draht / wire: Class F
Elektrode/ clip: 100% Sn

G Eigenschaften / general specifications:

Betriebstemp. / operating temperature: -40°C - + 125°C
Umgebungstemp. / ambient temperature: -40°C - + 85°C
It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.

Freigabe erteilt / general release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

MST	Version 2	04-10-11
MST	Version 1	04-07-28
Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.de

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744392200

LF




Bezeichnung : **SPEICHERDROSSEL WE-HCF**

description : **POWER-CHOKE WE-HCF**

DATUM / DATE : 2004-10-11

H Induktivitätskurve / Inductance curve :



Freigabe erteilt / general release:	Kunde / customer				
Datum / date	Unterschrift / signature				
	Würth Elektronik				
	MST	Version 2	04-10-11		
	MST	Version 1	04-07-28		
Geprüft / checked	Kontrolliert / approved		Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.de>

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744392200

LF




Bezeichnung : **SPEICHERDROSSEL WE-HCF**

description : **POWER-CHOKE WE-HCF**


DATUM / DATE : 2004-10-11

I Rollenspezifikation / tape and reel specification :

Gurtspezifikation / Tape specification:



A	16,0 ± 0,1	mm
B	1,50 ± 0,1	mm
C	4,00 ± 0,1	mm
W	24,0 ± 0,1	mm



Rollenspezifikation / Reel specification:

a	330,0 ± 0,5	mm
b	21,0 ± 0,8	mm
c	13,0 ± 0,5	mm
d	50,0 ± 0,5	mm

Freigabe erteilt / general release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

MST	Version 2	04-10-11
MST	Version 1	04-07-28
Name	Änderung / modification	Datum / date

This electronic component is designed and developed with the intention for use in general electronics equipments. Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network, where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body. In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before use. It is essential to give consideration when to install a protective circuit at the design stage.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.de