

Multilayer Ceramic Chip Capacitors, Qualified, Type CDR



ELECTRICAL SPECIFICATIONS

Note: Electrical characteristics at + 25 °C unless otherwise specified.

Capacitance Range: 1.0 pF to 0.47 µF

Voltage - Temperature Limits:

BP: 0 ± 30 ppm/°C from - 55 °C to + 125 °C, with 0 Vdc applied

BX: ± 15 % from - 55 °C to + 125 °C, with 0 Vdc applied

BX: + 15, - 25 % from - 55 °C to + 125 °C, with 100 % rated Vdc applied

Dissipation Factor (DF):

BP: 0.15 % maximum; BX: 2.5 % maximum

Test Frequency: 1 MHz ± 50 kHz for BP capacitors ≤ 1000 pF
and for BX capacitors ≤ 100 pF

All other BP and BX capacitors are tested at 1 kHz ± 50 Hz

FEATURES

- Military qualified products
- Federal stock control number, CAGE CODE 95275
- High reliability tested per MIL-PRF-55681
- Lead (Pb)-free applied for "Y" and "M" termination code
- Tin/Lead "Z" and "U" termination codes available



Available

RoHS*
COMPLIANT

Insulation Resistance (IR):


At + 25 °C and rated voltage 100 000 MΩ minimum or 1000 ΩF, whichever is less

Dielectric Withstanding Voltage (DWV):

This is the maximum voltage the capacitors are tested for a 1 to 5 second period and the charge/discharge current does not exceed 50 mA.

≤ 100 Vdc: DWV at 250 % of rated voltage

DIMENSIONS in inches [millimeters]



MIL-PRF-55681	STYLE	LENGTH (L)	WIDTH (W)	THICKNESS (T) (Max.)	TERM. (P)	
					(Min.)	(Max.)
/1	CDR01	0.080 ± 0.015 [2.03 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.055 [1.40]	0.010 [0.25]	0.030 [0.76]
	CDR02	0.180 ± 0.015 [4.57 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.055 [1.40]	0.010 [0.25]	0.030 [0.76]
	CDR03	0.180 ± 0.015 [4.57 ± 0.38]	0.080 ± 0.015 [2.03 ± 0.38]	0.080 [2.03]	0.010 [0.25]	0.030 [0.76]
	CDR04	0.180 ± 0.015 [4.57 ± 0.38]	0.125 ± 0.015 [3.20 ± 0.38]	0.080 [2.03]	0.010 [0.25]	0.030 [0.76]
/3	CDR06	0.220 ± 0.010 [5.59 ± 0.25]	0.250 ± 0.010 [6.35 ± 0.25]	0.045 [1.14]	0.010 [0.25]	0.030 [0.76]
/7	CDR31	0.078 ± 0.008 [2.00 ± 0.20]	0.049 ± 0.008 [1.25 ± 0.20]	0.051 [1.30]	0.012 [0.30]	0.028 [0.70]
/8	CDR32	0.125 ± 0.008 [3.20 ± 0.20]	0.062 ± 0.008 [1.60 ± 0.20]	0.051 [1.30]	0.012 [0.30]	0.028 [0.70]
/9	CDR33	0.125 ± 0.010 [3.20 ± 0.25]	0.098 ± 0.010 [2.50 ± 0.25]	0.059 [1.50]	0.010 [0.25]	0.030 [0.76]
/10	CDR34	0.176 ± 0.010 [4.50 ± 0.25]	0.125 ± 0.010 [3.20 ± 0.25]	0.059 [1.50]	0.010 [0.25]	0.030 [0.76]
/11	CDR35	0.176 ± 0.012 [4.50 ± 0.30]	0.250 ± 0.012 [6.40 ± 0.30]	0.059 [1.50]	0.008 [0.20]	0.032 [0.80]

ORDERING INFORMATION - MILITARY

CDR31	BX	102	A	K	Y	S	A	T
MILITARY STYLES	DIELECTRIC	CAPACITANCE NOMINAL CODE	DC VOLTAGE RATING ¹⁾	CAPACITANCE TOLERANCE	TERMINATION	FAILURE RATE	MARKING	PACKAGING
CDR01 CDR02 CDR03 CDR04 CDR06 CDR31 CDR32 CDR33 CDR34 CDR35	BP and BX	Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. Examples: 102 = 1000 pF 1R8 = 1.8 pF	A = 50 V B = 100 V	C = ± 0.25 pF D = ± 0.5 pF F = ± 1 % J = ± 5 % K = ± 10 % M = ± 20 %	Y = Ni barrier with 100 % tin W = Ni barrier with 100 % tin or tin/lead plate with min. 4 % lead Z = Ni barrier with tin/lead plate min. 4 % lead M = AgPd U = Base metallization-barrier metal-solder coated (tin/lead alloy, with a minimum of 4 % lead). Solder has a melting point of + 200 °C or less. Solder coat thickness is a minimum of 69 microinches.	M = 1.0 % P = 0.1 % R = 0.01 % S = 0.001 % Consult factory for failure rate status	A = Unmarked	T = 7" reel/plastic tape J = 7" reel/plastic tape (low qty) C = 7" reel/paper tape R = 11 1/4" reel/plastic tape P = 11 1/4" reel/paper tape B = Bulk

Note

1. DC voltage rating should not be exceeded in application
2. MIL-PRF 55681 "U" Termination part number code for CDR product length, width and thickness dimensions positive tolerances (including bandwidth) above are allowed to increase by the following amounts:

	Length	Width/Thickness
CDR01	0.020 [0.51]	0.015 [0.38]
CDR02-06	0.025 [0.64]	0.015 [0.38]
CDR31-35	0.023 [0.60]	0.012 [0.30]

* Pb containing terminations are not RoHS compliant, exemptions may apply



MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR01BP					
CDR01BP100B_ _ _	100	10	J, K	BP	100
CDR01BP120BJ_ _ _	120	12	J	BP	100
CDR01BP150B_ _ _	150	15	J, K	BP	100
CDR01BP180BJ_ _ _	180	18	J	BP	100
CDR01BP220B_ _ _	220	22	J, K	BP	100
CDR01BP270BJ_ _ _	270	27	J	BP	100
CDR01BP330B_ _ _	330	33	J, K	BP	100
CDR01BP390BJ_ _ _	390	39	J	BP	100
CDR01BP470B_ _ _	470	47	J, K	BP	100
CDR01BP560BJ_ _ _	560	56	J	BP	100
CDR01BP680B_ _ _	680	68	J, K	BP	100
CDR01BP820BJ_ _ _	820	82	J	BP	100
CDR01BP101B_ _ _	101	100	J, K	BP	100
CDR01B-121B_ _ _	121	120	J, K	BP, BX	100
CDR01B-151B_ _ _	151	150	J, K	BP, BX	100
CDR01B-181B_ _ _	181	180	J, K	BP, BX	100
CDR01BX					
CDR01BX221B_ _ _	221	220	K, M	BX	100
CDR01BX271BK_ _ _	271	270	K	BX	100
CDR01BX331B_ _ _	331	330	K, M	BX	100
CDR01BX391BK_ _ _	391	390	K	BX	100
CDR01BX471B_ _ _	471	470	K, M	BX	100
CDR01BX561BK_ _ _	561	560	K	BX	100
CDR01BX681B_ _ _	681	680	K, M	BX	100
CDR01BX821BK_ _ _	821	820	K	BX	100
CDR01BX102B_ _ _	102	1000	K, M	BX	100
CDR01BX122BK_ _ _	122	1200	K	BX	100
CDR01BX152B_ _ _	152	1500	K, M	BX	100
CDR01BX182BK_ _ _	182	1800	K	BX	100
CDR01BX222B_ _ _	222	2200	K, M	BX	100
CDR01BX272BK_ _ _	272	2700	K	BX	100
CDR01BX332B_ _ _	332	3300	K, M	BX	100
CDR01BX392AK_ _ _	392	3900	K	BX	50
CDR01BX472A_ _ _	472	4700	K, M	BX	50
CDR02BP					
CDR02BP221B_ _ _	221	220	J, K	BP	100
CDR02BP271BJ_ _ _	271	270	J	BP	100
CDR02BX					
CDR02BX392BK_ _ _	392	3900	K	BX	100
CDR02BX472B_ _ _	472	4700	K, M	BX	100
CDR02BX562BK_ _ _	562	5600	K	BX	100
CDR02BX682B_ _ _	682	6800	K, M	BX	100
CDR02BX822BK_ _ _	822	8200	K	BX	100
CDR02BX103B_ _ _	103	10 000	K, M	BX	100
CDR02BX123AK_ _ _	123	12 000	K	BX	50
CDR02BX153A_ _ _	153	15 000	K, M	BX	50
CDR02BX183AK_ _ _	183	18 000	K	BX	50
CDR02BX223A_ _ _	223	22 000	K, M	BX	50

MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR03BP					
CDR03BP331B_ _ _	331	330	J, K	BP	100
CDR03BP391BJ_ _	391	390	J	BP	100
CDR03BP471B_ _ _	471	470	J, K	BP	100
CDR03BP561BJ_ _	561	560	J	BP	100
CDR03BP681B_ _ _	681	680	J, K	BP	100
CDR03BP821BJ_ _	821	820	J	BP	100
CDR03BP102B_ _ _	102	1000	J, K	BP	100
CDR03BX					
CDR03BX123BK_ _	123	12 000	K	BX	100
CDR03BX153B_ _ _	153	15 000	K, M	BX	100
CDR03BX183BK_ _	183	18 000	K	BX	100
CDR03BX223B_ _ _	223	22 000	K, M	BX	100
CDR03BX273BK_ _	273	27 000	K	BX	100
CDR03BX333B_ _ _	333	33 000	K, M	BX	100
CDR03BX393AK_ _	393	39 000	K	BX	50
CDR03BX473A_ _ _	473	47 000	K, M	BX	50
CDR03BX563AK_ _	563	56 000	K	BX	50
CDR03BX683A_ _ _	683	68 000	K, M	BX	50
CDR04BP					
CDR04BP122BJ_ _	122	1200	J	BP	100
CDR04BP152B_ _ _	152	1500	J, K	BP	100
CDR04BP182BJ_ _	182	1800	J	BP	100
CDR04BP222B_ _ _	222	2200	J, K	BP	100
CDR04BP272BJ_ _	272	2700	J	BP	100
CDR04BP332B_ _ _	332	3300	J, K	BP	100
CDR04BX					
CDR04BX393BK_ _	393	39 000	K	BX	100
CDR04BX473B_ _ _	473	47 000	K, M	BX	100
CDR04BX563BK_ _	563	56 000	K	BX	100
CDR04BX823AK_ _	823	82 000	K	BX	50
CDR04BX104A_ _ _	104	100 000	K, M	BX	50
CDR04BX124AK_ _	124	120 000	K	BX	50
CDR04BX154A_ _ _	154	150 000	K, M	BX	50
CDR04BX184AK_ _	184	180 000	K	BX	50
CDR06BX					
CDR06BX394AK_ _	394	390 000	K	BX	50
CDR06BX474A_ _ _	474	470 000	K, M	BX	50
CDR31BP					
CDR31BP1R0B_ _ _	1R0	1	C	BP	100
CDR31BP1R1B_ _ _	1R1	1.1	C	BP	100
CDR31BP1R2B_ _ _	1R2	1.2	C	BP	100
CDR31BP1R3B_ _ _	1R3	1.3	C	BP	100
CDR31BP1R5B_ _ _	1R5	1.5	C	BP	100
CDR31BP1R6B_ _ _	1R6	1.6	C	BP	100



MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR31BP					
CDR31BP1R8B_ _ _	1R8	1.8	C	BP	100
CDR31BP2R0B_ _ _	2R0	2	C	BP	100
CDR31BP2R2B_ _ _	2R2	2.2	C	BP	100
CDR31BP2R4B_ _ _	2R4	2.4	C	BP	100
CDR31BP2R7B_ _ _	2R7	2.7	C, D	BP	100
CDR31BP3R0B_ _ _	3R0	3	C, D	BP	100
CDR31BP3R3B_ _ _	3R3	3.3	C, D	BP	100
CDR31BP3R6B_ _ _	3R6	3.6	C, D	BP	100
CDR31BP3R9B_ _ _	3R9	3.9	C, D	BP	100
CDR31BP4R3B_ _ _	4R3	4.3	C, D	BP	100
CDR31BP4R7B_ _ _	4R7	4.7	C, D	BP	100
CDR31BP5R1B_ _ _	5R1	5.1	C, D	BP	100
CDR31BP5R6B_ _ _	5R6	5.6	C, D	BP	100
CDR31BP6R2B_ _ _	6R2	6.2	C, D	BP	100
CDR31BP6R8B_ _ _	6R8	6.8	C, D	BP	100
CDR31BP7R5B_ _ _	7R5	7.5	C, D	BP	100
CDR31BP8R2B_ _ _	8R2	8.2	C, D	BP	100
CDR31BP9R1B_ _ _	9R1	9.1	C, D	BP	100
CDR31BP100B_ _ _	100	10	F, J, K	BP	100
CDR31BP110B_ _ _	110	11	F, J, K	BP	100
CDR31BP120B_ _ _	120	12	F, J, K	BP	100
CDR31BP130B_ _ _	130	13	F, J, K	BP	100
CDR31BP150B_ _ _	150	15	F, J, K	BP	100
CDR31BP160B_ _ _	160	16	F, J, K	BP	100
CDR31BP180B_ _ _	180	18	F, J, K	BP	100
CDR31BP200B_ _ _	200	20	F, J, K	BP	100
CDR31BP220B_ _ _	220	22	F, J, K	BP	100
CDR31BP240B_ _ _	240	24	F, J, K	BP	100
CDR31BP270B_ _ _	270	27	F, J, K	BP	100
CDR31BP300B_ _ _	300	30	F, J, K	BP	100
CDR31BP330B_ _ _	330	33	F, J, K	BP	100
CDR31BP360B_ _ _	360	36	F, J, K	BP	100
CDR31BP390B_ _ _	390	39	F, J, K	BP	100
CDR31BP430B_ _ _	430	43	F, J, K	BP	100
CDR31BP470B_ _ _	470	47	F, J, K	BP	100
CDR31BP510B_ _ _	510	51	F, J, K	BP	100
CDR31BP560B_ _ _	560	56	F, J, K	BP	100
CDR31BP620B_ _ _	620	62	F, J, K	BP	100
CDR31BP680B_ _ _	680	68	F, J, K	BP	100
CDR31BP750B_ _ _	750	75	F, J, K	BP	100
CDR31BP820B_ _ _	820	82	F, J, K	BP	100
CDR31BP910B_ _ _	910	91	F, J, K	BP	100

MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR31BP					
CDR31BP101B_ _ _	101	100	F, J, K	BP	100
CDR31BP111B_ _ _	111	110	F, J, K	BP	100
CDR31BP121B_ _ _	121	120	F, J, K	BP	100
CDR31BP131B_ _ _	131	130	F, J, K	BP	100
CDR31BP151B_ _ _	151	150	F, J, K	BP	100
CDR31BP161B_ _ _	161	160	F, J, K	BP	100
CDR31BP181B_ _ _	181	180	F, J, K	BP	100
CDR31BP201B_ _ _	201	200	F, J, K	BP	100
CDR31BP221B_ _ _	221	220	F, J, K	BP	100
CDR31BP241B_ _ _	241	240	F, J, K	BP	100
CDR31BP271B_ _ _	271	270	F, J, K	BP	100
CDR31BP301B_ _ _	301	300	F, J, K	BP	100
CDR31BP331B_ _ _	331	330	F, J, K	BP	100
CDR31BP361B_ _ _	361	360	F, J, K	BP	100
CDR31BP391B_ _ _	391	390	F, J, K	BP	100
CDR31BP431B_ _ _	431	430	F, J, K	BP	100
CDR31BP471B_ _ _	471	470	F, J, K	BP	100
CDR31BP511A_ _ _	511	510	F, J, K	BP	50
CDR31BP561A_ _ _	561	560	F, J, K	BP	50
CDR31BP621A_ _ _	621	620	F, J, K	BP	50
CDR31BP681A_ _ _	681	680	F, J, K	BP	50
CDR31BX					
CDR31BX471B_ _ _	471	470	K, M	BX	100
CDR31BX561B_ _ _	561	560	K, M	BX	100
CDR31BX681B_ _ _	681	680	K, M	BX	100
CDR31BX821B_ _ _	821	820	K, M	BX	100
CDR31BX102B_ _ _	102	1000	K, M	BX	100
CDR31BX122B_ _ _	122	1200	K, M	BX	100
CDR31BX152B_ _ _	152	1500	K, M	BX	100
CDR31BX182B_ _ _	182	1800	K, M	BX	100
CDR31BX222B_ _ _	222	2200	K, M	BX	100
CDR31BX272B_ _ _	272	2700	K, M	BX	100
CDR31BX332B_ _ _	332	3300	K, M	BX	100
CDR31BX392B_ _ _	392	3900	K, M	BX	100
CDR31BX472B_ _ _	472	4700	K, M	BX	100
CDR31BX562A_ _ _	562	5600	K, M	BX	50
CDR31BX682A_ _ _	682	6800	K, M	BX	50
CDR31BX822A_ _ _	822	8200	K, M	BX	50
CDR31BX103A_ _ _	103	10 000	K, M	BX	50
CDR31BX123A_ _ _	123	12 000	K, M	BX	50
CDR31BX153A_ _ _	153	15 000	K, M	BX	50
CDR31BX183A_ _ _	183	18 000	K, M	BX	50



MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR32BP					
CDR32BP1R0B_ _ _	1R0	1	C	BP	100
CDR32BP1R1B_ _ _	1R1	1.1	C	BP	100
CDR32BP1R2B_ _ _	1R2	1.2	C	BP	100
CDR32BP1R3B_ _ _	1R3	1.3	C	BP	100
CDR32BP1R5B_ _ _	1R5	1.5	C	BP	100
CDR32BP1R6B_ _ _	1R6	1.6	C	BP	100
CDR32BP1R8B_ _ _	1R8	1.8	C	BP	100
CDR32BP2R0B_ _ _	2R0	2	C	BP	100
CDR32BP2R2B_ _ _	2R2	2.2	C	BP	100
CDR32BP2R4B_ _ _	2R4	2.4	C	BP	100
CDR32BP2R7B_ _ _	2R7	2.7	C, D	BP	100
CDR32BP3R0B_ _ _	3R0	3	C, D	BP	100
CDR32BP3R3B_ _ _	3R3	3.3	C, D	BP	100
CDR32BP3R6B_ _ _	3R6	3.6	C, D	BP	100
CDR32BP3R9B_ _ _	3R9	3.9	C, D	BP	100
CDR32BP4R3B_ _ _	4R3	4.3	C, D	BP	100
CDR32BP4R7B_ _ _	4R7	4.7	C, D	BP	100
CDR32BP5R1B_ _ _	5R1	5.1	C, D	BP	100
CDR32BP5R6B_ _ _	5R6	5.6	C, D	BP	100
CDR32BP6R2B_ _ _	6R2	6.2	C, D	BP	100
CDR32BP6R8B_ _ _	6R8	6.8	C, D	BP	100
CDR32BP7R5B_ _ _	7R5	7.5	C, D	BP	100
CDR32BP8R2B_ _ _	8R2	8.2	C, D	BP	100
CDR32BP9R1B_ _ _	9R1	9.1	C, D	BP	100
CDR32BP100B_ _ _	100	10	F, J, K	BP	100
CDR32BP110B_ _ _	110	11	F, J, K	BP	100
CDR32BP120B_ _ _	120	12	F, J, K	BP	100
CDR32BP130B_ _ _	130	13	F, J, K	BP	100
CDR32BP150B_ _ _	150	15	F, J, K	BP	100
CDR32BP160B_ _ _	160	16	F, J, K	BP	100
CDR32BP180B_ _ _	180	18	F, J, K	BP	100
CDR32BP200B_ _ _	200	20	F, J, K	BP	100
CDR32BP220B_ _ _	220	22	F, J, K	BP	100
CDR32BP240B_ _ _	240	24	F, J, K	BP	100
CDR32BP270B_ _ _	270	27	F, J, K	BP	100
CDR32BP300B_ _ _	300	30	F, J, K	BP	100
CDR32BP330B_ _ _	330	33	F, J, K	BP	100
CDR32BP360B_ _ _	360	36	F, J, K	BP	100
CDR32BP390B_ _ _	390	39	F, J, K	BP	100
CDR32BP430B_ _ _	430	43	F, J, K	BP	100
CDR32BP470B_ _ _	470	47	F, J, K	BP	100
CDR32BP510B_ _ _	510	51	F, J, K	BP	100
CDR32BP560B_ _ _	560	56	F, J, K	BP	100
CDR32BP620B_ _ _	620	62	F, J, K	BP	100

MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR32BP					
CDR32BP680B_ _ _	680	68	F, J, K	BP	100
CDR32BP750B_ _ _	750	75	F, J, K	BP	100
CDR32BP820B_ _ _	820	82	F, J, K	BP	100
CDR32BP910B_ _ _	910	91	F, J, K	BP	100
CDR32BP101B_ _ _	101	100	F, J, K	BP	100
CDR32BP111B_ _ _	111	110	F, J, K	BP	100
CDR32BP121B_ _ _	121	120	F, J, K	BP	100
CDR32BP131B_ _ _	131	130	F, J, K	BP	100
CDR32BP151B_ _ _	151	150	F, J, K	BP	100
CDR32BP161B_ _ _	161	160	F, J, K	BP	100
CDR32BP181B_ _ _	181	180	F, J, K	BP	100
CDR32BP201B_ _ _	201	200	F, J, K	BP	100
CDR32BP221B_ _ _	221	220	F, J, K	BP	100
CDR32BP241B_ _ _	241	240	F, J, K	BP	100
CDR32BP271B_ _ _	271	270	F, J, K	BP	100
CDR32BP301B_ _ _	301	300	F, J, K	BP	100
CDR32BP331B_ _ _	331	330	F, J, K	BP	100
CDR32BP361B_ _ _	361	360	F, J, K	BP	100
CDR32BP391B_ _ _	391	390	F, J, K	BP	100
CDR32BP431B_ _ _	431	430	F, J, K	BP	100
CDR32BP471B_ _ _	471	470	F, J, K	BP	100
CDR32BP511B_ _ _	511	510	F, J, K	BP	100
CDR32BP561B_ _ _	561	560	F, J, K	BP	100
CDR32BP621B_ _ _	621	620	F, J, K	BP	100
CDR32BP681B_ _ _	681	680	F, J, K	BP	100
CDR32BP751B_ _ _	751	750	F, J, K	BP	100
CDR32BP821B_ _ _	821	820	F, J, K	BP	100
CDR32BP911B_ _ _	911	910	F, J, K	BP	100
CDR32BP102B_ _ _	102	1000	F, J, K	BP	100
CDR32BP112A_ _ _	112	1100	F, J, K	BP	50
CDR32BP122A_ _ _	122	1200	F, J, K	BP	50
CDR32BP132A_ _ _	132	1300	F, J, K	BP	50
CDR32BP152A_ _ _	152	1500	F, J, K	BP	50
CDR32BP162A_ _ _	162	1600	F, J, K	BP	50
CDR32BP182A_ _ _	182	1800	F, J, K	BP	50
CDR32BP202A_ _ _	202	2000	F, J, K	BP	50
CDR32BP222A_ _ _	222	2200	F, J, K	BP	50
CDR32BX					
CDR32BX472B_ _ _	472	4700	K, M	BX	100
CDR32BX562B_ _ _	562	5600	K, M	BX	100
CDR32BX682B_ _ _	682	6800	K, M	BX	100
CDR32BX822B_ _ _	822	8200	K, M	BX	100
CDR32BX103B_ _ _	103	10 000	K, M	BX	100
CDR32BX123B_ _ _	123	12 000	K, M	BX	100
CDR32BX153B_ _ _	153	15 000	K, M	BX	100
CDR32BX183A_ _ _	183	18 000	K, M	BX	50
CDR32BX223A_ _ _	223	22 000	K, M	BX	50
CDR32BX273A_ _ _	273	27 000	K, M	BX	50
CDR32BX333A_ _ _	333	33 000	K, M	BX	50
CDR32BX393A_ _ _	393	39 000	K, M	BX	50



MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR33BP					
CDR33BP102B_ _ _	102	1000	F, J, K	BP	100
CDR33BP112B_ _ _	112	1100	F, J, K	BP	100
CDR33BP122B_ _ _	122	1200	F, J, K	BP	100
CDR33BP132B_ _ _	132	1300	F, J, K	BP	100
CDR33BP152B_ _ _	152	1500	F, J, K	BP	100
CDR33BP162B_ _ _	162	1600	F, J, K	BP	100
CDR33BP182B_ _ _	182	1800	F, J, K	BP	100
CDR33BP202B_ _ _	202	2000	F, J, K	BP	100
CDR33BP222B_ _ _	222	2200	F, J, K	BP	100
CDR33BP242A_ _ _	242	2400	F, J, K	BP	50
CDR33BP272A_ _ _	272	2700	F, J, K	BP	50
CDR33BP302A_ _ _	302	3000	F, J, K	BP	50
CDR33BP332A_ _ _	332	3300	F, J, K	BP	50
CDR33BX					
CDR33BX153B_ _ _	153	15 000	K, M	BX	100
CDR33BX183B_ _ _	183	18 000	K, M	BX	100
CDR33BX223B_ _ _	223	22 000	K, M	BX	100
CDR33BX273B_ _ _	273	27 000	K, M	BX	100
CDR33BX393A_ _ _	393	39 000	K, M	BX	50
CDR33BX473A_ _ _	473	47 000	K, M	BX	50
CDR33BX563A_ _ _	563	56 000	K, M	BX	50
CDR33BX683A_ _ _	683	68 000	K, M	BX	50
CDR33BX823A_ _ _	823	82 000	K, M	BX	50
CDR33BX104A_ _ _	104	100 000	K, M	BX	50
CDR34BP					
CDR34BP222B_ _ _	222	2200	F, J, K	BP	100
CDR34BP242B_ _ _	242	2400	F, J, K	BP	100
CDR34BP272B_ _ _	272	2700	F, J, K	BP	100
CDR34BP302B_ _ _	302	3000	F, J, K	BP	100
CDR34BP332B_ _ _	332	3300	F, J, K	BP	100
CDR34BP362B_ _ _	362	3600	F, J, K	BP	100
CDR34BP392B_ _ _	392	3900	F, J, K	BP	100
CDR34BP432B_ _ _	432	4300	F, J, K	BP	100
CDR34BP472B_ _ _	472	4700	F, J, K	BP	100
CDR34BP512A_ _ _	512	5100	F, J, K	BP	50
CDR34BP562A_ _ _	562	5600	F, J, K	BP	50
CDR34BP622A_ _ _	622	6200	F, J, K	BP	50
CDR34BP682A_ _ _	682	6800	F, J, K	BP	50
CDR34BP752A_ _ _	752	7500	F, J, K	BP	50
CDR34BP822A_ _ _	822	8200	F, J, K	BP	50
CDR34BP912A_ _ _	912	9100	F, J, K	BP	50
CDR34BP103A_ _ _	103	10 000	F, J, K	BP	50

MIL-C-55681 QUALIFIED, TYPE CDR					
MILITARY TYPE DESIGNATION	CAPACITANCE CODE	CAPACITANCE (pF)	CAPACITANCE TOLERANCE	RATED TEMP. AND VOLTAGE TEMP. LIMITS	VOLTAGE (DC)
CDR34BX					
CDR34BX273B_ _ _	273	27 000	K, M	BX	100
CDR34BX333B_ _ _	333	33 000	K, M	BX	100
CDR34BX393B_ _ _	393	39 000	K, M	BX	100
CDR34BX473B_ _ _	473	47 000	K, M	BX	100
CDR34BX563B_ _ _	563	56 000	K, M	BX	100
CDR34BX104A_ _ _	104	100 000	K, M	BX	50
CDR34BX124A_ _ _	124	120 000	K, M	BX	50
CDR34BX154A_ _ _	154	150 000	K, M	BX	50
CDR34BX184A_ _ _	184	180 000	K, M	BX	50
CDR35BP					
CDR35BP472B_ _ _	472	4700	F, J, K	BP	100
CDR35BP512B_ _ _	512	5100	F, J, K	BP	100
CDR35BP562B_ _ _	562	5600	F, J, K	BP	100
CDR35BP622B_ _ _	622	6200	F, J, K	BP	100
CDR35BP682B_ _ _	682	6800	F, J, K	BP	100
CDR35BP752B_ _ _	752	7500	F, J, K	BP	100
CDR35BP822B_ _ _	822	8200	F, J, K	BP	100
CDR35BP912B_ _ _	912	9100	F, J, K	BP	100
CDR35BP103B_ _ _	103	10 000	F, J, K	BP	100
CDR35BP113A_ _ _	113	11 000	F, J, K	BP	50
CDR35BP123A_ _ _	123	12 000	F, J, K	BP	50
CDR35BP133A_ _ _	133	13 000	F, J, K	BP	50
CDR35BP153A_ _ _	153	15 000	F, J, K	BP	50
CDR35BP163A_ _ _	163	16 000	F, J, K	BP	50
CDR35BP183A_ _ _	183	18 000	F, J, K	BP	50
CDR35BP203A_ _ _	203	20 000	F, J, K	BP	50
CDR35BP223A_ _ _	223	22 000	F, J, K	BP	50
CDR35BX					
CDR35BX563B_ _ _	563	56 000	K, M	BX	100
CDR35BX683B_ _ _	683	68 000	K, M	BX	100
CDR35BX823B_ _ _	823	82 000	K, M	BX	100
CDR35BX104B_ _ _	104	100 000	K, M	BX	100
CDR35BX124B_ _ _	124	120 000	K, M	BX	100
CDR35BX154B_ _ _	154	150 000	K, M	BX	100
CDR35BX184A_ _ _	184	180 000	K, M	BX	50
CDR35BX224A_ _ _	224	220 000	K, M	BX	50
CDR35BX274A_ _ _	274	270 000	K, M	BX	50
CDR35BX334A_ _ _	334	330 000	K, M	BX	50
CDR35BX394A_ _ _	394	390 000	K, M	BX	50
CDR35BX474A_ _ _	474	470 000	K, M	BX	50



TAPE AND REEL QUANTITIES ^{1/2/3)}								
			7" REEL QUANTITIES			11 1/4" AND 13" REEL QUANTITIES		BULK
STYLES	BODY SIZE	TAPE SIZE	"C"	"T"	"J"	"P"	"R"	"B"
CDR01, CDR31	0805	8 mm	3000	3000	1000	10 000	10 000	100
CDR32	1206	8 mm	N/A	3000	1000	N/A	10 000	100
CDR33	1210	8 mm	N/A	3000	1000	N/A	10 000	100
CDR02	1805	12 mm	N/A	3000	500	N/A	10 000	100
CDR03	1808	12 mm	N/A	3000	500	N/A	10 000	100
CDR04, CDR34	1812	12 mm	N/A	1000	500	N/A	5000	100
CDR35	1825	12 mm	N/A	1000	500	N/A	5000	100
CDR06	2225	12 mm	N/A	1000	500	N/A	5000	100

Note

1. Vishay Vitramon uses embossed plastic carrier tape and punched paper carrier tape
2. Paper tape is not available for case sizes > 1206 or for component thickness > 0.035" [0.89 mm]
3. DC Voltage rating should not be exceeded in application



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.