CLOCK OSCILLATORS

SMD-version 5V

model	KXO-97
frequency range in MHz	1,80 ~ 50,0 MHz
frequency stability at -20° ~ +70°C at -40° ~ +85°C	 ± 50 ppm ± 100 ppm
operating temperature	standard -20° ~ +70°C available -40° ~ +85°C (=KXO-97T)
storage temperature	-40° ~ +85°C
symmetry	50% ± 10% at 1,4V DC level or ½ Vcc level
rise & fall time max.	TTL: 6 ns CMOS: 10 ns
"O" level max.	+ 0,4V (TTL) + 0,5V (CMOS)
"1" level min.	+2,4 (TTL) Vcc -0,5V (CMOS)
input voltage Vcc	+ 5V DC ± 10%
input current	10 mA
output load	10 TTL gates CMOS: 50 pF
start up time max.	10 ms
tristate funcion	yes
enable/disable delay time	100 ns max.
reflow soldering cond.	10 seconds max. at + 240°C
lead-free	yes
contents of reel	1000 pcs.
order no.	12.94200 ~ 12.94599





PIN	CONNECTION	
1	"L" (0V)	"H" (+5V) or OPEN
2	GND	
3	Z	OUTPUT
4	Vcc	

Z: high impedance



Suggested soldering pad





Reflow soldering condition







12/2004